

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant: Jean-Michel ROSSET,)
 et al.)
) Group: Not yet assigned
 Serial No.: Not yet assigned) Examiner: Not yet assigned
 Filed: Concurrently herewith) Our Ref: B-4198 618840-8
 For: "A COMMUNICATION PLATFORM)
 FOR PROVIDING COMPUTER TELEPHONY)
 INTEGRATION SERVICES TO REMOTE)
 SUBSCRIBERS, AND ASSOCIATED)
 METHOD") Date: June 5, 2001

JCS72 U.S. PTO
 09/875462
 06/05/01

CLAIM TO PRIORITY UNDER 35 U.S.C. 119

Commissioner of Patents and Trademarks
 Box New Patent Application
 Washington, D.C. 20231

Sir:

[X] Applicants hereby make a right of priority claim under 35
 U.S.C. 119 for the benefit of the filing date(s) of the
 following corresponding foreign application(s):


<u>COUNTRY</u>	<u>FILING DATE</u>	<u>SERIAL NUMBER</u>
EP	July 24, 2000	00410080.6

[] A certified copy of each of the above-noted patent
 applications was filed with the Parent Application
 No. _____.

[X] To support applicants' claim, a certified copy of the above-
 identified foreign patent application is enclosed herewith.

[] The priority document will be forwarded to the Patent Office
 when required or prior to issuance.

Respectfully submitted,



Richard P. Berg
 Attorney for Applicant
 Reg. No. 28,145

LADAS & PARRY
 5670 Wilshire Boulevard
 Suite 2100
 Los Angeles, CA 90048
 Telephone: (310) 934-2300
 Telefax: (213) 934-0202

THIS PAGE BLANK (USPTO)



Europäisches
Patentamt

European
Patent Office

Office européen
des brevets

JC872 U.S. PTO
09/875462
06/05/01

Bescheinigung

Certificate

Attestation

Die angehefteten Unterla-
gen stimmen mit der
ursprünglich eingereichten
Fassung der auf dem näch-
sten Blatt bezeichneten
europäischen Patentanmel-
dung überein.

The attached documents
are exact copies of the
European patent application
described on the following
page, as originally filed.

Les documents fixés à
cette attestation sont
conformes à la version
initialement déposée de
la demande de brevet
européen spécifiée à la
page suivante.

Patentanmeldung Nr. Patent application No. Demande de brevet n°

00410080.6

Der Präsident des Europäischen Patentamts:
Im Auftrag

For the President of the European Patent Office

Le Président de l'Office européen des brevets
p.o.

I.L.C. HATTEN-HECKMAN

DEN HAAG, DEN
THE HAGUE,
LA HAYE, LE

03/10/00

THIS PAGE BLANK (USPTO)



Europäisches
Patentamt

European
Patent Office

Office européen
des brevets

Blatt 2 der Bescheinigung
Sheet 2 of the certificate
Page 2 de l'attestation

Anmeldung Nr.:
Application no.:
Demande n°: 00410080.6

Anmeldetag:
Date of filing: 24/07/00
Date de dépôt:

Anmelder:
Applicant(s):
Demandeur(s):
Hewlett-Packard Company, A Delaware Corporation
Palo Alto, CA 94304
UNITED STATES OF AMERICA

Bezeichnung der Erfindung:
Title of the invention:
Titre de l'invention:

A communication platform for providing computer telephony integration services to remote subscribers, and associated method

In Anspruch genommene Priorität(en) / Priority(ies) claimed / Priorité(s) revendiquée(s)

Staat:
State:
Pays:

Tag:
Date:
Date:

Aktenzeichen:
File no.
Numéro de dépôt:

Internationale Patentklassifikation:
International Patent classification:
Classification internationale des brevets:

/

Am Anmeldetag benannte Vertragsstaaten:
Contracting states designated at date of filing: AT/BE/CH/CY/DE/DK/ES/FI/FR/GB/GR/IE/IT/LI/LU/MC/NL/PT/SE
Etats contractants désignés lors du dépôt:

Bemerkungen:
Remarks:
Remarques:

THIS PAGE BLANK (USPTO)

A Communication Platform for Providing Computer Telephony Integration Services
to Remote Subscribers, and Associated Method

5 The present invention generally relates to computer/telephony integration, and more particularly to an architecture and related method for obtaining computer/telephony integration (such as value-added voice services, convergent voice-data services, etc.) with certain improved properties.

Background of the invention

10

The concepts of "Intelligent Networks" and "Advanced Intelligent Network" are known as involving an architecture to implement services such as intelligent call routing on a public telephony network. This technology comprises basically a routing database coupled in a quite direct manner to the telephone network. However, these
15 services are mostly limited to voice telephony and have little or no interaction with the user's information systems.

There are also known so-called "Web Intelligent Networks" which have the purpose of solving some of the disadvantages of the classical intelligent network architecture by affording greater interactivity. It allows interaction between a subscriber's
20 information system and a service control point (SCP) of an intelligent network via the Internet. By means of such interaction, the subscriber has control over the service execution. (see "Integrating the Intelligent Network and the Internet", O'Connell et al, ICIN 96).

25

Further, so-called computer telephony integration (CTI) technologies offer a wide range of solutions to integrate telephony with computers. CTI applications are numerous and include call-centers, unified messaging (basically text messages available together with voice messages through a single interface), interactive voice
30 response systems, voice browsing systems, automatic call distribution, real time data fetch according to caller identification etc. However all standard CTI solutions are

operated on customer premises equipment (CPE). Therefore, they require the subscriber to connect their computer equipment to the telephone network via PBXs or via special telephony interface cards.

5 A major drawback of such CTI applications is that the function of flexible call routing permitted by the intelligent network technologies is not available when such applications are CPE-based. The reason is that CTI processing is always done after the call has been delivered by the network.

10 Another known technology is the so-called network or virtual call centers, which provide network-based CTI solutions for call centers. Such technology allows the subscriber to globally control the routing functions of the network (including automatic call distribution) e.g. for routing calls among different sites of the subscriber.

15 Still another prior art is constituted by a tentative project by a consortium named "Parlay" (See parlay white papers at the Internet address www.parlay.org). Such project defines programming interfaces to implement services that control the network behavior. Such interfaces have the purpose of allowing to control the
20 network behavior from software located in the subscriber's information system. However, this Parlay project only defines a programmatic API (Application Programming Interface, and implies that a suitable pre-existing intelligent network infrastructure is available that is capable of providing gateways between the network and the subscriber information system.

25

Summary of the present invention

A main objective of the present invention is to combine the generic and flexible character of CTI-based solutions to integrate telephony services with computer
30 equipment and information systems, while enabling to deliver advanced telephony functions in a similar way as intelligent network techniques.

Another objective of the present invention is to provide a very cost-effective alternative to the deployment of classical intelligent network infrastructure, specially for small and medium-sized telecom service providers.

5

Still another objective of the present invention is to eliminate the need for costly CPE-based equipment, like PABXs or CTI platforms, and to provide subscribers with greater flexibility while minimizing costly and therefore risky financial investments.

10

Yet another object is to provide the subscriber with additional resources such as voice processing, billing, etc. and to allow a subscriber (typically a voice/data service provider) to integrate telephony services with data or application services and to resell high-value convergent voice/data services.

15

According to a first aspect, the present invention provides a communication platform for providing computer/telephony integration services to remote subscribers, characterized in that it comprises:

20

- a hosted call switching unit in communication with an external telephone network or interconnected networks through a communications trunk;

25

- for each subscriber, a subscriber telephony component executed by processing means belonging to the communication platform and connected to an external subscriber's information system through a permanent private secure data channel, whereby said subscriber telephony component can communicate in a private manner with other information system components of said subscriber so as to be logically part of said information system, each subscriber component being capable of controlling said switching unit according to subscriber data;

- common resources available to each subscriber telephony component in association with call processing;

- means for allocating resources to each telephone call handled by a subscriber telephony component in response to data communication with said component through a secure interface.

5 Preferred but non-limiting aspects of this communication platform are as follows:

* each subscriber telephony component is comprised of an intelligent agent.

* said permanent private secure data channel is a virtual private network link (VPN) connected to a network of the subscriber's information system.

10 * said switching unit is capable of redirecting towards the telephone system of a given subscriber incoming calls intended to said subscriber through said communication trunk.

* said switching unit is capable of redirecting towards the computer system of a given subscriber incoming calls intended to said subscriber through said private
15 secure data channel.

* the communication platform further comprises:

- call handling resources available to each of said subscriber telephony components,
- a storage for resource allocation data in association with each subscriber telephony component, and

20 - control means for allocating call handling resources to a given subscriber telephony component when handling a telephone call on the basis of said resource allocation data.

* said call handling resources comprise voice processing resources.

* said voice processing resources are connected to said switching unit.

25 * the communication platform further comprises a billing system in communication with said control means for billing each subscriber according to call handling resource usage.

* the communication platform further comprises at least one hosted switch hardware platform comprising:

30 - said processing means for executing at least one subscriber telephony component,
- said hosted call switching unit, and

50004267

- control means for controlling said switching unit according to instructions by said executed subscriber telephony components.

According to a second aspect, the present invention provides a method for providing
5 computer telephony integration to a subscriber, comprising the following steps:

- providing a hardware communication platform, said communication platform comprising a hosted call switching unit in communication with an external telephone network or interconnected networks through a communications trunk, and call handling resources,
- 10 - installing a subscriber telephony component for execution on said communication platform,
- providing a permanent private secure data channel between said subscriber telephony component in said communication platform and an external information system of said subscriber,
- 15 - for each incoming call intended for the subscriber, directing said call to said communication platform,
- allocating call handling resources of said communication platform to said subscriber telephony component for handling said incoming call.

20 Preferred but non-limiting aspects of the above method are as follows:

* the method further comprises, before the call handling resources allocation step, a step of checking from resource allocation data stored by the communication platform whether there are sufficient call handling resources available for the current
25 incoming call.

* the method further comprises the additional step of periodically computing a bill to the subscriber according to call handling resource usage by the associated subscriber telephone component.

* the method further comprises, in association with said installation step, the
30 additional step of allocating to the subscriber telephone component security data for secure communications with said subscriber information system.

* the method further comprises, in association with said installation step, the additional step of allocating to the subscriber telephone component security data for secure communications between said component and the rest of said communication platform.

5

Brief description of the drawings

The present invention will now be described in greater detail with reference to the appended drawings, in which

10

Figure 1 is a block diagram of a telephony network, subscriber information system and communication platform embodying the present invention,

15

Figure 2 is a block diagram of a practical embodiment of a computer telephony integration system according to the prior art, and

Figure 3 is a block diagram of a practical embodiment of a computer telephony integration system according to the present invention.

20

Detailed description of a preferred embodiment

I - Architecture description

Figure 1 illustrates a general architecture implementing the present invention.

25

1. Communication platform

The present invention is mainly embodied by a communication platform 100 for providing telecommunication value added services to subscribers.

30

The communication platform comprises the following elements:

50004267

a) hosted switch 110

This is a computer-based node connected to a set of interconnected telephony
5 networks 200 through interconnection trunks 300, in a manner known per se. The
basic function of the hosted switch is to process and switch incoming calls that are
routed to its switching array 114 via the telephony trunks. Action on the switching
array 114 is performed by a User Telephony Agent 111, as will be described in the
following, via a call control unit 113.

10

b) voice processing resources 120

These are additional computer resources which can be used in combination with the
hosted switch to perform advanced voice processing functions such as voice
15 synthesis, automatic voice recognition, etc.

c) billing system 130

This is a computer system that collects resource usage per subscriber and generates
20 billing information.

d) subscriber management database 140

This is another computer-based system that stores subscription information for each
25 subscriber of the services afforded by the communication platform.

e) access control management system 150

The basic function of this system is to supervise resource allocation control to user
30 telephony agents, as they will be described in the following, and to track resource

usage. This system can physically belong to the hosted switch hardware or it can be implemented on a separate computer system and control several hosted switches.

f) operational support system

5

This is a computer system that provides management and supervision information to the communication platform operators in order to insure the proper operations of the whole platform.

10 2. Operating environment

a) interconnection

15 The communication platform is interconnected to the telecommunication networks 200 at the hosted switch level using telephony voice trunks 300, as indicated above. Regarding the trunk technology, conventional, state-of-the-art TDM (time division multiplexing) trunks can be used together with SS7 signaling or Voice over Internet Protocol (IP) trunks, using H323 or signaling according to the standard Session Invitation Protocol (SIP).

20

The communication platform 100 can either be deployed as a telephony network of its own, e.g., it is operated by a competitive local extension carrier (CLEC) that handles the interconnection with a separate, e.g. national network. Alternatively, it can be deployed as a sub-network or a Service Node. In the latter case, it may be 25 connected as an adjunct node to classic switching systems or as an overlay of several nodes, in a manner known per se.

b) user Access

30 Reference 400 globally designates the subscriber's computer and telephone system including a number of conventional computers 410 connected together via an

Intranet-type network 420. Reference 440 globally designates the telephony system of the subscriber, which is connected to the telephone network 200 via one or several lines 500. The computer system 410, 420 of the subscriber is connected to the hosted switch platform 110 of the communication platform 100 via a multiplexer 430
5 connected to one end of a so-called virtual private network (VPN) link 600, the other end of which is connected to the hosted switch 110 as will be described in greater detail below.

10 It can be seen that the hosted switch 110 has no access to the telephony local loop of the subscriber. Instead it has a data communication to the user over the Internet via said VPN link 600.

15 This VPN link is used for data communication between a user telephony agent 111 hosted by the hosted switch 110 and the subscriber information system 410, 420.

It should be noted that, when the hosted switch needs to establish a voice communication (e.g. an outside call redirection) towards a called party in the subscriber system 400 (as will be described below in greater detail), the hosted switch has two options :

- 20 - either it redirects the call towards a switching node or a third-party network (i.e. via network 200) that has a wireline or a radio connection to the called party;
- or it uses packetized voice over the VPN link 600 if a sufficient bandwidth is available on this link and if the subscriber system 400 has the necessary equipment to receive voice calls over a data network (Internet telephony).

25

c) User Telephony Agents

30 "Intelligent Agents" are a recent concept in software engineering. Detailed information about such agents is available e.g. on the Web site www.agent.org.

Agents are generally described as software entities that:

- execute autonomously with an internal representation of their user needs,
- communicate with other agents or with the user according to predefined schemes;
- monitor the state of their operating environment.

5 An important feature of the present invention is that the communication platform 100 uses User Telephony Agents (UTAs) 111 to provide network-based CTI services to subscribers (typically one UTA per subscriber).

From a hardware standpoint, each UTA is hosted by the hosted switch platform 110
10 to handle calls on behalf of the subscriber.

From the standpoint of software components, UTAs are logically part of the respective subscribers' information systems 410, 420. This is performed by a Telephony Agent hosting service provider 112 included in the hosted switch platform
15 110 and which provides a secured remote extension of the user's Intranet 420 via the above described VPN link 600 and multiplexer 430.

The main function of an UTA is to handle incoming telephone calls on behalf of the respective subscriber, using as necessary the call processing and voice processing
20 resources available in the communication platform 100. The basic call control is performed by a call control unit 113 connected to the switching array 114.

Advantageously standard computer telephony application and programming interfaces (APIs), for instance interfaces such as Java Telephony Application and
25 Programming Interfaces (JTAPI) or Java Intelligent Network (JAIN) interfaces, known per se, are provided in the hosted switch's telephony agent hosting service provider 112 and used for ensuring suitable interface between the agents 111 and the hosting service provider 112.

30 The voice processing resources 120 available in the communication platform 110 can be used by an UTA to interact with the caller in various ways, for instance to play or

record announcements, to recognize DTMF signals, synthesize or recognize live voice, etc.

Another important aspect of the present invention is the ability of the hosting service provider 112 to control resource access and track resource usage for each UTA 111.

More particularly, each hosted UTA has corresponding resource allocation information stored in correspondence therewith in the subscriber management database 140, so that the UTA, via the access control management system 150, is prevented from using more resources than the user subscription permits.

Additionally, detailed records of resource usage (logging) by each UTA 111 are kept by the access control management system 150, e.g. for billing purposes by the billing system 130.

15

II - Services description

First of all, each user telephony agent is a piece of software that must have been developed according to the subscriber requirements, and tested. This step involves standard software engineering activities that is outside the scope of the present invention. The starting point of the services provision is the UTA software code of a given subscriber.

20

Service provisioning involves the following steps:

25

1. UTA Packaging

Each time a new subscriber wants his UTA to be hosted by the communication platform 100, a process designated as UTA packaging is executed for combining the UTA code with authentication information so that the communication platform can

30

perform appropriate security checking before safely letting the UTA use the communication platform resources.

UTA authentication has a double goal:

5

- allowing the communication platform to check whether the code it is loading from the subscriber environment 400 is coming from a trusted and well-known source; this is done by appropriate, well known signature techniques;

10 - allowing the UTA to set up a secure connection to the User's Intranet 420 via the VPN link 600; this is performed by providing the UTA with appropriate security certificates, encryption keys or equivalent in connection with corresponding means in the corresponding subscriber's information system 410, 420.

15 2. Subscription providing

In association with the installation of the UTA 111 of a new subscriber, the communication platform's subscriber database 140 must be configured with corresponding subscription information so that the access control manager 150 can
20 let the UTA use call-processing or voice-processing resources within the limits of the subscription.

This subscription information includes for instance the following information:

- basic telephony resources allocated to a subscriber: mostly phone numbers and the
25 number of lines (i.e. how many calls a UTA may simultaneously handle);
- processing resources available to the UTA; as explained above, the communication platform controls all the resources used by an UTA, including CPU and memory (RAM, hard disk, etc.) usage, call and voice processing resources and networking resources at the VPN link level. The resources available to UTA to handle calls on a
30 predefined number of lines are therefore provisioned to the Subscriber database.

3. Service Activation

When the steps described above have been successfully completed, the UTA is activated and the communication platform can start delivering and emitting calls to
5 and from this UTA. These operations include the following:

a) incoming calls

10 Incoming calls are routed through the interconnection trunks 300 to the hosted switch which is in charge of handling the call (it should be noted in this regard that a communication platform may include several hosted switch platforms 110 each hosting several UTAs 111, so that an incoming call from network 200 first has to be routed to the appropriate platform 110).

15 The access control management system 150 then checks that the UTA of the subscriber to which this incoming call is intended has sufficient authorized resource capabilities to handle this incoming call in addition to other calls currently handled. If so, the call is delivered to the UTA.

20 The UTA then requests the appropriate resource allocation to handle the call. The UTA may choose to:

- use local voice processing resources 120 of platform 100 to play announcements, record messages, interact with the caller using DTMF or automatic speech recognition, etc.;
- 25 - cross-connect the call to another telephone address, inside or outside the communication platform (e.g. call bridging);
- perform a sequence involving a combination of the above two possibilities.

Again, for each resource consumed by the UTA, the access control manager system
30 150 checks whether the UTA's allowed resources are sufficient.

When the call is complete, all the resources allocated to this call are released. The access control management system 150 then issues a report to the billing system 130 that keeps a history of resource consumption.

- 5 It should be noted here that, since the access control management system has real-time knowledge of resource usage for each UTA, prepaid billing schemes can be easily implemented.

10 As the UTA operates within the subscriber's information system 400 from the logical standpoint, it may interact in real time or close to real time with other agents or data (or more generally software components) located within anywhere in this information system. Of course, such interaction during the handling of an incoming call should be performed with sufficient speed to avoid any undesirable latency in providing vocal information to the caller after hanging off.

15

For avoiding such risk of latency without being dependent from e.g. abnormally low bandwidth at the VPN link 600 The communication platform can also provide local, caching storage to the UTA to satisfy latency requirements when serving large numbers of callers.

20

b) outgoing calls

25 The UTA 111 can also issue outgoing calls. Such calls are either handled by automatic voice processing resources 120 or connected to live agents through Voice over Internet Protocol (VoIP). An example of such application is the management of outgoing - outgoing to the telephone network, that is -marketing calls, preferably with predictive dialing techniques known per se.

30 Resource allocation and billing for outgoing calls is preferably similar or identical to the ones for incoming calls.

III - Practical comparative example

A comparison between a standard CTI architecture and a CTI agent-based set-up according to the present invention will now be made with particular reference to
5 Figures 2 and 3 in a practical application of voice browsing. In Figures 2 and 3, identical or similar parts as those of Figure 1 are designated as far as possible by the same reference signs.

1. Voice browsing application using classic CTI

10

The basic purpose of a voice browsing application is to provide information stored in electronic form to callers. It allows the caller to navigate in the available information using the DTMF tones generated by his telephone keyboard or automatic voice recognition.

15

Voice is one medium to access information amongst many others (such as PC-based navigators, WAP telephones, Personal Digital Assistants, etc.), and a voice browsing application is typically designed using the well-known multi-tiered IP architecture as shown in Figure 2.

20

Such architecture, entirely located at the subscriber premises, includes a first tier 450 of voice access services, a middle tier 411 of information services (typically business application services) and an final tier 412 of storage information services (typically data servers). The first tier 450 includes the voice browsing application itself 451,
25 CTI middleware 452 and CTI hardware 453 for connection to the public telephone network 200.

More precisely, the first tier 450 houses the whole CTI hardware and software, with the following (known per se) features:

- 30 - telephony access: telephone lines are pulled either directly from the telephony operator (in analog, or ISDN format) or indirectly via a PABX system;

- telephony lines are connected to a computer system via telephony cards; depending on the number of telephony ports that need to be handled by the system, telephony cards may connect e.g. 1 to 4 telephony ports or 1 to 4 E1/ T1 multiplexed ports that connect up to 120 ports;

- 5 - voice processing functions provide automatic interaction with the caller; in the present example of a voice browsing application, these voice processing functions involve: information presentation e.g. text to speech, and information transfer to the telephony line and caller interaction via either DTMF tone or speech recognition; in most cases, these functions are handled by standard computers assisted by dedicated
10 hardware.

2. Voice Browsing using inventive agent-based CTI

The communication platform 100 as described with reference to Figure 1 allows a
15 service provider to virtualize the voice front-end part of the voice browsing applications, as shown in Figure 3.

The hosted switch 110, located in the network, hosts the voice browsing front-end and can access the needed specialized voice processing resources located in the
20 communication platform (not shown in its entirety in Figure 3).

Telephony lines are no longer terminated at the user site. Instead, the VPN link 600 extends the User's Intranet (420) to the remote hosted switch 110.

25 For callers, there is no difference between the two architectures. In both cases, the voice services can be provided using for instance geographic numbers, 800-type free phone numbers, shared revenue numbers, etc...

It is understood from the foregoing that the communication platform according to the
30 present invention is suitable for providing network based, hosted CTI services.

More particularly, the communication platform allows to combine the values of:

- CTI technologies that permit the integration of communication services to the user's electronic information systems,

- intelligent network architectures that permit flexible and customized call routing schemes,

- hosted application services that reduce the capital needs for specific and often costly resources and provide a greater flexibility to adapt communication resources to instantaneous business needs.

10 Practical examples are numerous. For instance, the present invention allows an Internet service provider to provide, in addition to data services, vocal services (e.g. for unified messaging) which will be handled at the communication platform level, i.e. without major investments and with effective costs for the provider that will be substantially proportional to resource usage.

15

Another example is the capacity of the communication platform to allocate to a given User Telephony Agent different resources (including the number of available lines for incoming or outgoing calls) as a function of time.

20

THIS PAGE BLANK (USPTO)

CLAIMS

1. A communication platform for providing computer/telephony integration services to remote subscribers, characterized in that it comprises:
- 5 - a hosted call switching unit in communication with an external telephone network or interconnected networks through a communications trunk;
- for each subscriber, a subscriber telephony component executed by processing means belonging to the communication platform and connected to an external subscriber's information system through a permanent private secure data channel,
- 10 whereby said subscriber telephony component can communicate in a private manner with other information system components of said subscriber so as to be logically part of said information system, each subscriber component being capable of controlling said switching unit according to subscriber data;
- resources available to each subscriber telephony component in association with call
- 15 processing or routing;
- means for allocating resources to each telephone call handled by a subscriber telephony component in response to data communication with said component through a secure interface.
- 20 2. A communication platform according to claim 1, wherein each subscriber telephony component is comprised of an intelligent agent.
3. A communication platform according to claim 1 or 2, wherein said permanent private secure data channel is a virtual private network link (VPN)
- 25 connected to a network of the subscriber's information system.
4. A communication platform according to claim 1, wherein said switching unit is capable of redirecting towards the telephone system of a given subscriber incoming calls intended to said subscriber through said communication trunk.

5. A communication platform according to claim 1, wherein said switching unit is capable of redirecting towards the computer system of a given subscriber incoming calls intended to said subscriber through said private secure data channel.

5 6. A communication platform according to claim 1, further comprising:
- call handling resources available to each of said subscriber telephony components,
- a storage for resource allocation data in association with each subscriber telephony component, and
- control means for allocating call handling resources to a given subscriber telephony
10 component when handling a telephone call on the basis of said resource allocation data.

7. A communication platform according to claim 6, wherein said call handling resources comprise voice processing resources.

15 8. A communication platform according to claim 7, wherein said voice processing resources are connected to said switching unit.

9. A communication platform according to any one of claims 6 to 8, further
20 comprising a billing system in communication with said control means for billing each subscriber according to call handling resource usage.

10. A communication platform according to claim 1, comprising at least one hosted switch hardware platform comprising:
25 - said processing means for executing at least one subscriber telephony component,
- said hosted call switching unit, and
- control means for controlling said switching unit according to instructions by said executed subscriber telephony components.

30 11. A method for providing computer telephony integration to a subscriber, comprising the following steps:

50004267

- providing a hardware communication platform, said communication platform comprising a hosted call switching unit in communication with an external telephone network or interconnected networks through a communications trunk, and call handling resources,
 - 5 - installing a subscriber telephony component for execution on said communication platform,
 - providing a permanent private secure data channel between said subscriber telephony component in said communication platform and an external information system of said subscriber,
 - 10 - for each incoming call intended for the subscriber, directing said call to said communication platform,
 - allocating call handling resources of said communication platform to said subscriber telephony component for handling said incoming call.
- 15 12. A method according to claim 11, comprising, before the call handling resources allocation step, a step of checking from resource allocation data stored by the communication platform whether there are sufficient call handling resources available for the current incoming call.
- 20 13. A method according to claim 12, comprising the additional step of periodically computing a bill to the subscriber according to call handling resource usage by the associated subscriber telephone component.
- 25 14. A method according to claim 11, further comprising, in association with said installation step, the additional step of allocating to the subscriber telephone component security data for secure communications with said subscriber information system.
- 30 15. A method according to claim 11, further comprising, in association with said installation step, the additional step of allocating to the subscriber telephone

component security data for secure communications between said component and the rest of said communication platform.

“A communication platform for providing computer telephony integration services to remote subscribers, and associated method”


ABSTRACT OF THE DISCLOSURE

A communication platform for providing computer/telephony integration services to remote subscribers comprises:

- a hosted call switching unit (114) in communication with an external telephone network or interconnected networks (200) through a communications trunk (300);**
- for each subscriber, a subscriber telephony component (111) executed by processing means (110) belonging to the communication platform and connected to an external subscriber's information system (400) through a permanent private secure data channel (600), whereby said subscriber telephony component can communicate in a private manner with other information system components (410) of said subscriber so as to be logically part of said information system, each subscriber component being capable of controlling said switching unit (114) according to subscriber data ;**
- resources (120) available to each subscriber telephony component in association with call processing or routing;**
- means (150) for allocating resources to each telephone call handled by a subscriber telephony component (111) in response to data communication with said component through a secure interface (112).**

(Figure 1)

THIS PAGE BLANK (USPTO)

*Fig. 1*

2/3




Fig. 2
(PRIOR ART)




Fig. 3

THIS PAGE BLANK (USPTO)